

**TORQUE VALUES**

THREADS	ID'S	TORQUE SPECS
2 3/8 Reg	32mm	3,285 Ft/Lbs
2 3/8 IF	32mm	4,606 Ft/Lbs
2 3/8 HT SLH90	32mm	4,500 Ft/Lbs
2 7/8 Reg	32mm	5,766 Ft/Lbs
2 7/8 IF	32mm	7,390 Ft/Lbs
2 7/8 SLH90	32mm	4600 Ft/Lbs
(X/O for MWD )3 CDP	32mm	2,750 Ft/Lbs
533 HDR / 2 7/8 HYD	57mm	5,000 Ft/Lbs
3 1/2 IF	57mm	9,900 Ft/Lbs
4 1/2 Reg	57mm	21,600 Ft/Lbs
4 1/2 XH	71mm	22,426 Ft/Lbs
4 1/2 IF	71mm	23,500 Ft/Lbs
4 1/2 H90	71mm	23,159 Ft/Lbs
5 H90	71mm	29,400 Ft/Lbs
6 5/8 Reg	71mm	53,346 Ft/Lbs
7 H90	76mm	69,265 Ft/Lbs
7 5/8 Reg	76mm	88,580 Ft/Lbs

TORQUES MAY VARY DEPENDING ON ID